



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Aluminum clip with EPDM Gasket
- ③ EJT- Alum. Extruded Carrier Track (Black Anodized)
- ④ Z-Girt 12 Ga [50ksi Galvanized steel A653] (Not by NBK)
- ⑤ $\frac{1}{4}$ "-14 x $\frac{3}{4}$ " (6.3 x 19 mm) PPH S.S. fastener (Not by NBK)
- ⑥ $\frac{1}{4}$ "-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑦ Insulation per design (Not by NBK)
- ⑧ $\frac{5}{8}$ " GYP Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑨ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑩ Shim as required (Not by NBK)

SYSTEM: _____
TERRART 22 ECO

DETAIL: _____
STANDARD STUDWALL DETAIL

DETAIL NUMBER: _____
NBK-22-07

TILE DIRECTION: _____
HORIZONTAL

DRAWING REFERENCE: _____
TYPICAL INTERNAL CORNER

SCALE: _____
1:2

NBK | ARCHITECTURAL
 TERRACOTTA
 A Hunter Douglas Company

NBK North America
 10 Federal Street, Second Floor
 Salem, MA 01970
 Telephone: +1 (781) 639 2662
 www.nbkterracotta.com