



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Aluminum clip with EPDM Gasket
- ③ EVT- Alum. Extruded Carrier Track (Black Anodized)
- ④ Z-Girt 12 Ga [50ksi Galvanized steel A653] (Not by NBK)
- ⑤ 1/4"-14 x 3/4" (6.3 x 19 mm) PPH S.S. fastener (Not by NBK)
- ⑥ 1/4"-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑦ Insulation per design (Not by NBK)
- ⑧ 5/8" GYP Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑨ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ Shim as required (Not by NBK)

SYSTEM:	DETAIL:	DETAIL NUMBER:	<p>A Hunter Douglas Company</p> <p>NBK North America</p> <p>10 Federal Street, Second Floor Salem, MA 01970 Telephone: +1 (781) 639 2662 www.nbkterracotta.com</p>
22 TERRART ECO	STANDARD STUDWALL DETAIL	NBK-22-09	
TILE DIRECTIONS:	DRAWING REFERENCE:	SCALE:	
HORIZONTAL	TYPICAL PARAPET	1:2	