



- ① 28mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)

CLADDING ZONE PER DESIGN

1 1/8"  
[28 mm]

3/8"  
[9.5 mm]

<p>CLIENT:</p> <p><b>SCALE 1:2</b></p>	<p>PROJECT NUMBER:</p> <p>PROJECT:</p> <p><b>STANDARD DETAILS TERRAT 28</b></p>	<p>DRAWING NAME:</p> <p><b>STUDWALL DETAILS</b></p> <p>DRAWING REFERENCE:</p> <p><b>HORIZONTAL SECTION</b></p>	<p>PROJECT MANAGER:</p> <p>PRINT DATE - PRINT TIME:</p> <p><b>September 3, 2020 -- 07:54</b></p> <p>DATE:</p> <p><b>Juni 21, 2019</b></p> <p>SHEET NUMBER:</p> <p><b>NBK-28-01</b></p>	<p><b>NBK</b> ARCHITECTURAL TERRACOTTA <small>A Hunter Douglas Company</small></p> <hr/> <p><b>SALES &amp; OPERATIONS</b></p> <p>NBK North America 40 Tioga Way Suite 250 Mablehead MA 01945 US TELEPHONE: +1-781-630-2662 FAX: +1-781-630-9555</p>
--	---	--	--	---