



- ① 28mm thick NBK terracotta tile
- ③ VTS30/VTS31 - Alum. extruded carrier track
- ④ SGA - Alum. extruded subgirt-angle
- ⑤ SG - Alum. extruded sub-girt 24"
- ⑦ 1/4"-14 x 1" HWS #3 S.S Drill-flex or similar (Not by NBK)
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4"-14 x 2" Drill-flex or approved equal (Not by NBK)
- ⑱ TCLP30 NBK extruded clip

CLADDING PER DESIGN

1 1/8"
[28 mm]

3/8"
[10 mm]

SYSTEM: TERRART 28	DETAIL: STANDARD STUDWALL DETAIL	DETAIL NUMBER: NBK-HS-28-09	<p>NBK North America A Hunter Douglas Company</p> <p>10 Federal Street, Second Floor Salem, MA 01970 Telephone: +1 (781) 639 2662 www.nbkterracotta.com</p>
TILE DIRECTION: HORIZONTAL	DRAWING REFERENCE: TYPICAL PARAPET	SCALE: 1:2	
COPYRIGHT: © 2022 All rights reserved			