



- ① 28mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ BC Aluminum clips

PROJECT NUMBER: \_\_\_\_\_  
 CLIENT: **SCALE 1:2**  
 PROJECT: **STANDARD DETAILS TERRART 28**

DRAWING NAME: **STUDWALL DETAILS**  
 DRAWING REFERENCE: **TYPICAL EXP JOINT**

PROJECT MANAGER: \_\_\_\_\_  
 PRINT DATE - PRINT TIME: **September 3, 2020 -- 08:03**  
 DATE: **June 21, 2019**  
 SHEET NUMBER: **NBK-28-10**  
 REVISION: \_\_\_\_\_

**NBK** ARCHITECTURAL TERRACOTTA  
 A Hunter Douglas Company

**SALES & OPERATIONS**  
 NBK North America  
 40 Tioga Way Suite 250  
 Mablehead MA 01945 US  
 TELEPHONE: +1-781-639-2862  
 FAX: +1-781-639-8555