



- ① 30mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ JT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ WGK 01 Wiper gasket (Optional)

PROJECT NUMBER: \_\_\_\_\_

DRAWING NAME:  
**STUDWALL DETAILS**

PROJECT MANAGER:  
PRINT DATE - PRINT TIME:  
**September 3, 2020 -- 08:12**



CLIENT:  
**SCALE 1:2**

PROJECT:  
**STANDARD DETAILS  
TERRART 30**

DRAWING REFERENCE:  
**WINDOW JAMB**

DATE:  
**Juni 21, 2019**

**SALES & OPERATIONS**

SHEET NUMBER:  
**NBK-30-03**

REVISION:

REVISION:

NBK North America  
40 Tioga Way Suite 250  
Mablehead MA 01945 US  
TELEPHONE: +1-781-630-2662  
FAX: +1-781-630-9555