



- ① 30mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ BC Aluminum clips

CLIENT:	PROJECT NUMBER: PROJECT:	DRAWING NAME: <b>STUDWALL DETAILS</b>	PROJECT MANAGER: PRINT DATE - PRINT TIME: <b>September 3, 2020 -- 08:15</b>	
SCALE 1:2	STANDARD DETAILS <b>TERRART 30</b>	DRAWING REFERENCE: <b>TYPICAL EXP JOINT</b>	DATE: <b>June 21, 2019</b> SHEET NUMBER: <b>NBK-30-10</b>	SALES & OPERATIONS NBK North America 40 Tioga Way Suite 250 Mablehead MA 01945 US TELEPHONE: +1-781-630-2662 FAX: +1-781-630-9555