



- ① 40mm thick NBK terracotta tile
- ③ VTS30/VTS31 - Alum. extruded carrier track
- ④ SGA - Alum. extruded subgirt-angle
- ⑤ SG - Alum. extruded sub-girt 24"
- ⑦ 1/4"-14 x 1" HWH S.S Bi-Flex or similar (Not by NBK)
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑱ TCLP40 NBK extruded clip

<p>SYSTEM: _____</p> <p>TERRART 40</p> <p>TILE DIRECTION: _____</p> <p>HORIZONTAL</p>	<p>DETAIL: _____</p> <p>STANDARD STUDWALL DETAIL</p> <p>DRAWING REFERENCE: _____</p> <p>TYPICAL PARAPET</p>	<p>DETAIL NUMBER: _____</p> <p>NBK-HS-40-09</p> <p>SCALE: _____</p> <p>1:2</p>
<p>NBK ARCHITECTURAL TERRACOTTA</p> <p>A Hunter Douglas Company</p> <hr/> <p>NBK North America</p> <p>10 Federal Street, Second Floor Salem, MA 01970 Telephone: +1 (781) 639 2662 www.nbkterracotta.com</p>		