



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK JTC Clip, Stainless Steel
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ 8" Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑧ Insulation Per Design (Not by NBK)
- ⑨ 5/8" GYP. Board Sheathing w/ Air & Vapor Barrier Membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

CLIENT: **SCALE 1/4"=1'**

PROJECT NUMBER: _____

PROJECT: **STANDARD DETAILS
TERRART ECO - VERTICAL**

DRAWING NAME: **STUDWALL DETAILS**

DRAWING REFERENCE: **TYPICAL PARAPET**

PROJECT MANAGER: _____

PRINT DATE - PRINT TIME: **May 11, 2020 - 16:43**

DATE: **May 4, 2020**

SHEET NUMBER: **NBK-ECO-09**

REVISION: _____

NBK ARCHITECTURAL
TERRACOTTA
A Hunter Douglas Company

SALES & OPERATIONS

NBK North America
40 Tioga Way Suite 250
Maplehead MA 01945 US
TELEPHONE: +1-781-393-9444
FAX: +1-281-628-9555