



- ① 28mm thick NBK terracotta tile
- ② CLP30 NBK extruded clip
- ③ VTS30/VTS31 Alum. extruded carrier track
- ④ SGA - Alum. extruded subgirt-angle
- ⑤ SG - Alum. extruded sub-girt 24"
- ⑥ GSK100 - EPDM spacer gasket
- ⑦ 1/4"-14 x 1" HWH S.S. Bi Flex or similar (Not by NBK)
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH S.S. Bi Flex or approved equal (Not by NBK)

SYSTEM: <b>TERRART 28</b>	DETAIL: <b>STANDARD STUDWALL DETAIL</b>	DETAIL NUMBER: <b>NBK-HS-28-02</b>
TILE DIRECTION: <b>HORIZONTAL</b>	DRAWING REFERENCE: <b>TYPICAL EX CORNER</b>	SCALE: <b>1:2</b>

**ARCHITECTURAL TERRACOTTA**  
 A Hunter Douglas Company

---

**NBK North America**

10 Federal Street, Second Floor  
 Salem, MA 01970  
 Telephone: +1 (781) 639 2662  
 www.nbkterracotta.com