


- ① 28mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ JT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ WGK 01 Wiper gasket (Optional)

| | | | | |
|------------------|--|--|---|--|
| CLIENT: | PROJECT NUMBER: PROJECT: | DRAWING NAME: STUDWALL DETAILS DRAWING REFERENCE: WINDOW JAMB | PROJECT MANAGER: PRINT DATE - PRINT TIME: September 3, 2020 -- 07:56 DATE: June 21, 2019 SHEET NUMBER: NBK-28-03 |  SALES & OPERATIONS NBK North America 40 Tioga Way Suite 250 Mablehead MA 01945 US TELEPHONE: +1-781-630-2662 FAX: +1-781-630-9555 |
| SCALE 1:2 | STANDARD DETAILS TERRART 28 | | | |