



- ① 28mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ JT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 3/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ WGK 01 Wiper gasket (Optional)

PROJECT NUMBER: _____
 CLIENT: _____
 PROJECT: **STANDARD DETAILS
 TERRART 28**

SCALE 1:2

DRAWING NAME: **STUDWALL DETAILS**
 DRAWING REFERENCE: **TYPICAL INTERNAL CORNER**

PROJECT MANAGER: _____
 PRINT DATE - PRINT TIME: **September 3, 2020 -- 08:09**
 DATE: **June 21, 2019**
 SHEET NUMBER: **NBK-28-14**
 REVISION: _____

NBK ARCHITECTURAL
 TERRACOTTA
 A Hunter Douglas Company

SALES & OPERATIONS
 NBK North America
 40 Tioga Way Suite 250
 Mablehead MA 01945 US
 TELEPHONE: +1-781-639-2862
 FAX: +1-781-639-8555