



- ① 30mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ BC Aluminum clips

PROJECT NUMBER: _____
 CLIENT: _____
SCALE 1:2

PROJECT: _____
**STANDARD DETAILS
 TERRART 30**

DRAWING NAME: _____
STUDWALL DETAILS

DRAWING REFERENCE: _____
TYPICAL SILL

PROJECT MANAGER: _____
 PRINT DATE - PRINT TIME: _____
September 3, 2020 -- 08:16

DATE: _____
June 21, 2019

SHEET NUMBER: _____
NBK-30-12

REVISION: _____

NBK ARCHITECTURAL
 TERRACOTTA
A Hunter Douglas Company

SALES & OPERATIONS

NBK North America
 40 Tioga Way Suite 250
 Mablehead MA 01945 US
 TELEPHONE: +1-781-630-2662
 FAX: +1-781-630-9555