



$\frac{1}{8}''$ [3.9 mm]
 $\frac{1}{8}''$ [3.9 mm]
 $\frac{1}{4}''$ [2 mm]

- ① 40mm thick NBK terracotta tile
- ② SCLP/ECLP - NBK clip, zinc casting
- ③ CVT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ $\frac{5}{8}''$ GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ $\frac{1}{4}''$ drill-flex, or approved equal (Not by NBK)
- ⑫ $\frac{1}{4}''$ -14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)

CLIENT _____ PROJECT NUMBER _____ PROJECT _____

DRAWING NAME: **STUDWALL DETAILS**
 DRAWING REFERENCE: **TYPICAL EX CORNER**

PROJECT MANAGER: _____
 PRINT DATE - PRINT TIME: **September 3, 2020 -- 08:20**



SCALE 1:2

STANDARD DETAILS
 TERRART 40

NBK-40-02

DATE: **June 21, 2019**
 SHEET NUMBER: **NBK-40-02**

SALES & OPERATIONS
 NBK North America
 40 Tioga Way Suite 250
 Mablehead MA 01945 US
 TELEPHONE: +1-781-630-2662
 FAX: +1-781-630-9555