



- ① 40mm thick NBK terracotta tile
- ② SCLP/ECLP - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S. drillflex or similar (Not by NBK)
- ⑬ BC Aluminum clips

CLADDING ZONE PER DESIGN

1 9/16"
[40 mm]

CLIENT: SCALE 1:2

PROJECT NUMBER:
PROJECT: STANDARD DETAILS
TERRART 40

DRAWING NAME:
STUDWALL DETAILS
TYPICAL PARAPET

DRAWING REFERENCE:

PROJECT MANAGER:
PRINT DATE - PRINT TIME:
September 3, 2020 -- 08:38
DATE:
Juni 21, 2019
SHEET NUMBER:
NBK-40-09
REVISION:

NBK ARCHITECTURAL
TERRACOTTA
A Hunter Douglas Company

SALES & OPERATIONS
NBK North America
40 Tioga Way Suite 250
Maldenhead, MA 02148 US
TELEPHONE: +1-781-639-2662
FAX: +1-781-639-8055