



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK JTC Clip, Stainless Steel
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ 8" Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑧ Insulation Per Design (Not by NBK)
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

SCALE 1/4"=1'

PROJECT NUMBER: _____
 PROJECT: **STANDARD DETAILS
 TERRART ECO - VERTICAL**

DRAWING NAME: **STUDWALL DETAILS**
 DRAWING REFERENCE: **TYPICAL EX CORNER**

PROJECT MANAGER: _____
 PRINT DATE - PRINT TIME: **May 11, 2020 - 16:40**
 DATE: **May 4, 2020**
 SHEET NUMBER: **NBK-ECO-02** DIVISION: _____

NBK ARCHITECTURAL
 TERRACOTTA
A Hunter Douglas Company

SALES & OPERATIONS
 NBK North America
 10 Federal Street, Second Floor
 Salem, MA 01970 US
 TELEPHONE: +1-781-839-9862
 FAX: +1-781-839-8055