



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Clip w/ Gasket, Aluminum
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ Continuous Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑧ Insulation Per Design (Not by NBK)
- ⑨ 5/8" GYP. Board Sheathing w/ Air & Vapor Barrier Membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

CLADDING ZONE PER DESIGN

3"

7/8" [22 mm]

3/8"

<p>CLIENT:</p> <p>SCALE 1/4"=1'</p>	<p>PROJECT NUMBER:</p> <p>PROJECT: STANDARD DETAILS TERRART ECO - HORIZONTAL</p>	<p>DRAWING NAME:</p> <p>STUDWALL DETAILS WINDOW JAMB</p> <p>DRAWING REFERENCE:</p>	<p>PROJECT MANAGER:</p> <p>PRINT DATE - PRINT TIME:</p> <p>March 12, 2020 -- 15:18</p> <p>DATE:</p> <p>March 12, 2020</p> <p>SHEET NUMBER:</p> <p>NBK-ECO-03</p>
			<p>NBK ARCHITECTURAL TERRACOTTA</p> <p>A Hunter Douglas Company</p> <hr/> <p>SALES & OPERATIONS</p> <p>NBK North America 10 Federal Street, Second Floor Salem, MA 01970 US TELEPHONE: +1-781-633-9962 FAX: +1-781-633-9955</p>