



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK JTC Clip, Stainless Steel
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ 8" Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑧ Insulation Per Design (Not by NBK)
- ⑨ 5/8" GYP. Board Sheathing w/ Air & Vapor Barrier Membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

PROJECT NUMBER: _____

CLIENT: **SCALE 1/4" = 1'**

PROJECT: **STANDARD DETAILS
TERRART ECO - VERTICAL**

DRAWING NAME: **STUDWALL DETAILS**

DRAWING REFERENCE: **VERTICAL SECTION**

PROJECT MANAGER: _____

PRINT DATE - PRINT TIME: **March 10, 2020 -- 14:49**

DATE: **March 9, 2020**

SHEET NUMBER: **NBK-ECO-04**

REVISION: _____



SALES & OPERATIONS

NBK North America
10 Federal Street, Second Floor
Salem, MA 01970 US
TELEPHONE: +1-781-839-9862
FAX: +1-781-839-8055