



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Clip w/ Gasket, Aluminum
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ Continuous Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑧ Insulation Per Design (Not by NBK)
- ⑨ 5/8" GYP. Board Sheathing w/ Air & Vapor Barrier Membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

| | | | | | |
|---|--|--|--|--|--|
| PROJECT NUMBER: _____ PROJECT: _____ | | DRAWING NAME: STUDWALL DETAILS | | PROJECT MANAGER: _____ | |
| CLIENT: _____ | | DRAWING REFERENCE: TYPICAL HEAD | | PRINT DATE - PRINT TIME: March 12, 2020 -- 15:22 | |
| SCALE 1/4"-1' | | STANDARD DETAILS TERRART ECO - HORIZONTAL | | DATE: March 12, 2020 | |
| | | | | SHEET NUMBER: NBK-ECO-11 | |
| | | | | DIVISION: _____ | |
| | | | | NBK ARCHITECTURAL TERRACOTTA <small>A Hunter Douglas Company</small> | |
| | | | | SALES & OPERATIONS <small>NBK North America 10 Federal Street, Second Floor Salem, MA 01970 US TELEPHONE: +1-781-633-9962 FAX: +1-781-633-9055</small> | |