



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Clip w/ Gasket, Aluminum
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ Continuous Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑤ NBK JTC Clip, Stainless Steel
- ⑧ Insulation Per Design (Not by NBK)
- ⑨ 5/8" GYP. Board Sheathing w/ Air & Vapor Barrier Membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

CLIENT: **SCALE 1/4"=1'**

PROJECT NUMBER: \_\_\_\_\_

PROJECT: **STANDARD DETAILS  
TERRART ECO - HORIZONTAL**

DRAWING NAME: **STUDWALL DETAILS**

DRAWING REFERENCE: **TYPICAL PARAPET (CUT TILE)**

PROJECT MANAGER: \_\_\_\_\_

PRINT DATE -- PRINT TIME: **August 25, 2020 - 17:27**

DATE: **May 11, 2020**

SHEET NUMBER: **NBK-ECO-16**

REVISIONS: \_\_\_\_\_

**NBK** ARCHITECTURAL  
TERRACOTTA  
A Hunter Douglas Company

**SALES & OPERATIONS**  
NBK North America  
40 Tloca Way Suite 250  
Mablehead MA 01945 US  
TELEPHONE: +1-781-339-9444  
FAX: +1-781-638-8555