



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Aluminum clip with EPDM Gasket
- ③ EVT- Alum. Extruded Carrier Track (Black Anodized)
- ④ Z-Girt 12 Ga [50ksi Galvanized steel A653] (Not by NBK)
- ⑤ 1/4"-14 x 3/4" (6.3 x 19 mm) PPH S.S. fastener (Not by NBK)
- ⑥ 1/4"-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑦ Insulation per design (Not by NBK)
- ⑧ 5/8" GYP Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑨ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ Shim as required (Not by NBK)

SYSTEM:  
**TERRART 22 ECO**

DETAIL:  
**STANDARD STUDWALL DETAIL**

DETAIL NUMBER:  
**NBK-22-10**

TILE DIRECTION:  
**HORIZONTAL**

DRAWING REFERENCE:  
**TYPICAL EXP/DEF JOINT**

SCALE:  
**1:2**

**NBK** | ARCHITECTURAL  
TERRACOTTA  
A Hunter Douglas Company

**NBK North America**

10 Federal Street, Second Floor  
Salem, MA 01970  
Telephone: +1- (781) 639 2662  
www.nbkterracotta.com