



- ① 28mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑭ BC Aluminum clips

PROJECT NUMBER: _____

CLIENT: _____

SCALE 1:2

DRAWING NAME: STUDWALL DETAILS

DRAWING REFERENCE: TYPICAL SILL

PROJECT: STANDARD DETAILS
TERRART 28

PROJECT MANAGER: _____

PRINT DATE - PRINT TIME: September 3, 2020 -- 08:06

DATE: _____

June 21, 2019

SHEET NUMBER: _____ REVISION: _____

NBK-28-12



SALES & OPERATIONS

NBK North America
40 Tioga Way Suite 250
Mablehead MA 01945 US
TELEPHONE: +1-781-639-2662
FAX: +1-781-639-8555