



- ① 28mm thick NBK terracotta tile
- ③ VTS30/VTS31 Alum. extruded carrier track
- ④ SGA - Alum. extruded subgirt-angle
- ⑤ SG - Alum. extruded sub-girt 24"
- ⑦ 1/4"-14 x 1" HWH S.S. Bi-Flex or similar (Not by NBK)
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑱ TCLP30 NBK extruded clip

CLADDING ZONE PER DESIGN

SYSTEM:
TERRART 28

DETAIL:
STANDARD STUDWALL DETAIL

DETAIL NUMBER:
NBK-HS-28-12a

TILE DIRECTION:
HORIZONTAL

DRAWING REFERENCE:
TYPICAL SILL

SCALE:
1:2

NBK | ARCHITECTURAL
TERRACOTTA
A Hunter Douglas Company

NBK North America

10 Federal Street, Second Floor
Salem, MA 01970
Telephone: +1 (781) 639 2662
www.nbkterracotta.com