



- ① 30mm thick NBK terracotta tile
- ② SCLP2/ECLP2 - NBK clip, zinc casting
- ③ VT- Alum. extruded carrier track
- ④ SGA-Alum. extruded subgirt-angle
- ⑤ SG-Alum. extruded sub-girt
- ⑥ GK401 - EPDM spacer gasket
- ⑦ NBK PVC spacer-PT-01
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4" drill-flex, or approved equal (Not by NBK)
- ⑫ 1/4" -14 x 1" HWS #3 S.S drillflex or similar (Not by NBK)
- ⑬ BC Aluminum clips

PROJECT NUMBER: _____
 CLIENT: _____
 SCALE 1:2
 STANDARD DETAILS
 TERRART 30

DRAWING NAME:
STUDWALL DETAILS
TYPICAL PARAPET
 DRAWING REFERENCE: _____

PROJECT MANAGER:
 PRINT DATE - PRINT TIME:
September 3, 2020 -- 08:14
 DATE:
Juni 21, 2019
 SHEET NUMBER:
NBK-30-09
 REVISION:

NBK | ARCHITECTURAL
 TERRACOTTA
 A Hunter Douglas Company

SALES & OPERATIONS
 NBK North America
 4D Tioga Way Suite 250
 Marblehead, MA 01945 U.S.
 TELEPHONE: +1-781-639-2662
 FAX: +1-781-639-055