



- ① 30mm thick NBK terracotta tile
- ③ VTS30/VTS31 Alum. extruded carrier track
- ④ SGA - Alum. extruded subgirt-angle
- ⑤ SG - Alum. extruded sub-girt 24"
- ⑦  $\frac{1}{4}$ "-14 x 1" HWH S.S Bi-Flex or similar (Not by NBK)
- ⑧ Insulation per design
- ⑨  $\frac{5}{8}$ " GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪  $\frac{1}{4}$ "-14 x 2" HWH S.S Bi-Flex or approved equal (Not by NBK)
- ⑱ TCLP40 NBK extruded clip

SYSTEM: \_\_\_\_\_  
**TERRART 40**

DETAIL: \_\_\_\_\_  
**STANDARD STUDWALL DETAIL**

DETAIL NUMBER: \_\_\_\_\_  
**NBK-HS-40-12a**

TILE DIRECTION: \_\_\_\_\_  
**HORIZONTAL**

DRAWING REFERENCE: \_\_\_\_\_  
**TYPICAL SILL**

SCALE: \_\_\_\_\_  
**1:2**

**NBK** | ARCHITECTURAL  
 TERRACOTTA  
 A Hunter Douglas Company

**NBK North America**

10 Federal Street, Second Floor  
 Salem, MA 01970  
 Telephone: +1 (781) 639 2662  
 www.nbkterracotta.com