



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Aluminum clip with EPDM Gasket
- ③ EJTB Alum. Extruded Carrier Track (Black Anodized)
- ④ Z-Girt 12 Ga [50ksi Galvanized steel A653] (Not by NBK)
- ⑤ 1/4"-14 x 3/4" (6.3 x 19 mm) PPH S.S. fastener (Not by NBK)
- ⑥ 1/4"-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑦ Insulation per design (Not by NBK)
- ⑧ 5/8" GYP Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑨ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑩ Shim as required (Not by NBK)

SYSTEM: TERRART 22 ECO	DETAIL: STANDARD STUDWALL DETAIL	DETAIL NUMBER: NBK-22-02
TILE DIRECTION: HORIZONTAL	DRAWING REFERENCE: TYPICAL EX CORNER	SCALE: 1:2

NBK | ARCHITECTURAL TERRACOTTA
 A Hunter Douglas Company

NBK North America
 10 Federal Street, Second Floor
 Salem, MA 01970
 Telephone: +1 (781) 639 2662
 www.nbkterracotta.com