



- ① 22mm NBK TERRART Eco Terracotta Tile
- ② NBK Extruded Clip w/ Gasket, Aluminum
- ③ VT- Alum. Extruded Carrier Track, Black Anodized
- ④ Continuous Z-Girt 16 Ga. [50 ksi] Galvanized Steel (Not by NBK)
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical Steel Stud Framing, min. 16 Ga. @ 16" O.C. (Not by NBK)
- ⑪ 1/4"-14 x 2" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑫ 1/4"-14 x 1" HWH #3 Drill Flex, or Approved Equal (Not by NBK)
- ⑬ Shim, As Required (Not by NBK)

CLIENT: **SCALE 1/4"=1'**

PROJECT: **STANDARD DETAILS
TERRART ECO - HORIZONTAL**

DRAWING NAME: **STUDWALL DETAILS**

DRAWING REFERENCE: **TYPICAL EX CORNER**

PROJECT MANAGER:

PRINT DATE - PRINT TIME: **March 12, 2020 -- 15:17**

DATE: **March 12, 2020**

SHEET NUMBER: **NBK-ECO-02**

REVISION:

NBK ARCHITECTURAL
TERRACOTTA
A Hunter Douglas Company

SALES & OPERATIONS

NBK North America
10 Federal Street, Second Floor
Salem, MA 01970 US
TELEPHONE: +1-781-633-9862
FAX: +1-781-633-9855