



- ① 30mm thick NBK terracotta tile
- ② CLP2822 - NBK Extruded clip
- ③ VTS30/VTS31 Alum. extruded carrier track
- ④ SGA - Alum. extruded subgirt-angle
- ⑤ SG - Alum. extruded sub-girt 24"
- ⑥ Insulation per design
- ⑦ 1/4"-14 x 1" HWS #3 S.S Drill-flex or similar (Not by NBK)
- ⑧ Insulation per design
- ⑨ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑩ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑪ 1/4"-14 x 2" Drill-flex or approved equal (Not by NBK)
- ⑫ JTC Stainless steel clip

SYSTEM: TERRART 40

DETAIL: STANDARD STUDWALL DETAIL

DETAIL NUMBER: NBK-HS-40-13b

TILE DIRECTION: HORIZONTAL

DRAWING REFERENCE: TYPICAL SILL - CUT TILE

SCALE: 1:2

NBK | ARCHITECTURAL
TERRACOTTA
A Hunter Douglas Company

NBK North America

10 Federal Street, Second Floor
Salem, MA 01970
Telephone: +1 (781) 639 2662
www.nbkterracotta.com