



- ① 28 mm thick NBK terracotta tile
- ② HTS30/HTS31 Alum. extruded carrier track
- ③ Extruded Aluminum Angle 6063 T6 2" x 2 1/2" x 3/16" x 0'-8"
- ④ Extruded Aluminum Angle 6063 T6 2" x 2 1/2" x 3/16" x 0'-6"
- ⑤ RS30/RS31 "shelf" clip
- ⑥ 1/4"-14 x 1" HWH S.S. Bi-Flex or similar (Not by NBK)
- ⑦ (3) 1/4"-20 x 1" HWH S.S. Bi-Flex or similar (Not by NBK)
- ⑧ 1/4"-14 x 2" HWH S.S. Bi-Flex or approved equal (Not by NBK)
- ⑨ Insulation per design (Not by NBK)
- ⑩ 5/8" GYP. Board sheathing with air & vapor barrier membrane (Not by NBK)
- ⑪ Vertical steel stud framing, min. 16 ga@ 16" centers (Not by NBK)
- ⑫ JTC clip - Anti-walking clip
- ⑬ Aluminum connecting angle

SYSTEM: TERRART 28	DETAIL: STANDARD STUDWALL DETAIL	DETAIL NUMBER: NBK-VS-28-08
TILE DIRECTION: VERTICAL	DRAWING REFERENCE: JAMB TILE	SCALE: 1:2

NBK | ARCHITECTURAL TERRACOTTA
 A Hunter Douglas Company

NBK North America
 10 Federal Street, Second Floor
 Salem, MA 01970
 Telephone: +1 (781) 639 2662
 www.nbkterracotta.com